FAY, SHARPE, FAGAN, MINNICH & MCKEE, LLP
1100 SUPERIOR AVE, 7TH FLOOR
CLEVELAND, OHIO 44114
PHONE 216-861-5582
FAX 216-241-1666

DATE: November 27, 2001
FILE: SFK 2 0002 PCT
RE: Preliminary Japanese Patent Search
EJO/kls

File 347:JAPIO OCT 1976-2001/JUL(UPDATED 011105)
(c) 2001 JPO & JAPIO
*File 347: JAPIO data problems with year 2000 records are now fixed.
Alerts have been run. See HELP NEWS 347 for details.

Set	Items	Description
S1	1	PN=JP 57185420

1/19/1
DIALOG(R)File 347:JAPIO

01035120 **Image available**
IMAGE PICKUP CONTROLLER

PUB. NO.: 57-185420 A]
PUBLISHED: November 15, 1982 (19821115)
INVENTOR(s): ONUMA TAKASHI
APPLICANT(s): CANON INC [000100] (A Japanese Company or Corporation), JP (Japan)
APPL. NO.: 56-070324 [JP 8170324]
FILED: May 11, 1981 (19810511)
INTL CLASS: [3] G03B-007/10; H04N-005/26
JAPIO CLASS: 29.1 (PRECISION INSTRUMENTS -- Photography & Cinematography); 29.2 (PRECISION INSTRUMENTS -- Optical Equipment); 44.6 (COMMUNICATION -- Television)
JOURNAL: Section: P, Section No. 174, Vol. 07, No. 32, Pg. 77, February 08, 1983 (19830208)

ABSTRACT

PURPOSE: To avoid a hunting phenomenon and at the same time to realize a forcible closing operation, by preventing the full stop-down operation by detecting the aperture value optained immediately before the aperature is

JOURNAL: Section: M, Section No. 169, Vol. 06, No. 220, Pg. 66,
November 05, 1982 (19821105)

ABSTRACT

PURPOSE: To achieve high-precision hemming work through one operation by using a work pattern consisting of a prelminary bending pattern surface and a primary bending pattern surface in one body to hem a work composed of an inner panel and an outer panel.

CONSTITUTION: To the lower pattern 1 of a hemming work device, a work 2 composed of an outer panel 2a and an inner panel 2b is fitted, and at its upper part, a work pattern 3 provided with a preliminary bending pattern surface 3a and a primary bending surface 3b successively is installed while energized by a spring 7 as shown by an arrow. The work pattern 3 is lowered to press the end part 2c of the outer panel 2a with the preliminary bending pattern surface 3a for preliminary bending work, and then the work pattern 3 is lowered to bring a slide cam 4 into slide contact with a driving cam 8. Consequently, the work pattern 3 is lowered while moving in the opposite direction to the arrow direction against a spring 7, and the primary bending pattern surface 3b performs the primary bending work of the end part 2c.



S3 0 PN=JP 788567

S4 4000 PD=19950404

4000 S4
4251 AU=YANAGIDA?
S5 3 S4 AND AU=YANAGIDA?

5/PN/1